

ESCO
HEALTHCARE



Streamline[®] Containment Isolator Class III

(Negative, Total Exhaust Model)

*Your Containment Solution for Infectious /
Biohazardous Material Handling*



SCI-2G8-N3SL-III-EG



SCI-3G8-N3SL-III-SS



Introduction

Streamline® Containment Isolator Class III (SCI Class III) provides the highest level of personnel, product, and environmental protection against highly infectious microbiological agents and other hazardous biosafety level (BSL) 2+ to BSL-4 materials by isolating the main process in a negatively pressured system.

Key Benefits

- World's most certified Class III Isolator BSC, Compliant to all international biosafety standards
- Class 3 Leak Tight Containment, as per ISO 10648-2
- ISO Class 5 air cleanliness as per ISO 14644-1
- Extreme negative pressure up to -125 Pa in Process Chamber enhancing operator and environment protection



SCI Electrogalvanized Steel Total Exhaust Unit*



SCI Stainless Steel Total Exhaust Unit*

Customized with BIBO Exhaust Filter below the work zone

Comparison between SCI - Class III and AC3 units

Product	Streamline® Containment Isolator - Class III (SCI Class III)	Product
Design	BS EN 12469, NIOSH, OSHA, NSF/ANSI 49-2016, YY0569 Chinese standards, ISO 14644-1:2015	EN 12469, Europe
Containment Applications	Pressure tested as per Class 3 leakage tightness (ISO 10648-2) and can undergo daily in-situ pressure testing	Not possible for in-situ pressure hold test
Glove Leak Test	Pressure leak test can be done daily via quantifiable glove integrity tester (optional accessory)	Not applicable
Downflow Velocity	SCI III standard design with enhanced integrated supply and exhaust fan able to achieve downflow velocity of 0.40m/s ± 20%	AC3 has no downflow velocity test as it does not have supply fan. It only has exhaust fan to create negative pressure in chamber.
Enhanced Ergonomics	Designed with a sloped front angle for enhanced ergonomics, and to allow personnel operation while seated and/or standing.	Ergonomically designed to allow personnel operation while in a seated position.
Controller	Sentinel™ Gold Microprocessor Controller	Sentinel™ Silver Microprocessor Controller
Pressure Display	Pressure value of process and pass chamber are displayed in the Sentinel™ Display	Pressure value of process chamber are displayed on Magnehelic Gauge
Pass box	Dynamic	Static

Main Features

- HEPA (H14) filters with a typical efficiency of >99.995% at 0.1 to 0.3 microns, providing ISO Class 5 air cleanliness as per ISO 14644-1.
- Bag-In, Bag-Out (BIBO) filters with standard Exhaust Connection
- Sentinel™ Gold Microprocessor controller supervises all functions and monitors airflow and pressure in real-time
- Work zone and pass-through interchange are under negative pressure to the room to maintain operator protection in the event of a breach in the barrier isolation system
- Robust dual-wall construction. Unique Esco Dynamic Chamber™ plenum surrounds filter seals with negative pressure
- Electromagnetic interlocking door with time delayed ingress/egress control to minimize particle entry; assuring work sterility during material transfer
- Ergonomically angled front to improve reach and operator comfort
- Leak-tested assembly guarantees maximum protection and flame and abrasion resistant
- FDA-grade air-tight compression
- Work zone without crevices and easy to clean
- With drain pan at the bottom
- Options for external material of construction:
 - Electrogalvanized steel with ISOCIDE™ powder coating
 - Full stainless steel 304 exterior
- Foot switch to easily access inner doors




Safety and Certification

	Design	Cabinet Performance	Air Cleanliness	Electrical Safety
Standard Compliance	BS EN 12469*, NIOSH, OSHA, NSF*/ANSI 49-2016, YY0569 Chinese standards*, ISO 14644-1:2015	Class 3 Leak Tight Containment as per ISO 10648-2, IESTRP-CC034.1, Worldwide CETA CAG-002-2006, NSF49:2002	ISO 14644-1, Class 5 (in operation), EU GMP Grade A, IESTG-CC1001, USA, IEST-G-CC1002, USA, IESTRP-CC007.1, Worldwide, IEST-RP-CC001.3, Worldwide	IEC 61010-1, Worldwide EN 61010-1, Europe UL 61010-1, USA CAN/CSA-22.2, No. 61010-1

All components used in Esco products meet or exceed all applicable safety requirements.

* To comply with biosafety standards, NSF 49, BS EN 12469, YY0569 Chinese standards, or other local standards, the unit must be linked to external blower or building exhaust to meet each standard's negative pressure requirement.



- HEPA-filtered air
- Unfiltered/potentially contaminated air
- Room air / inflow air

The **Streamline® Containment Isolator Class III (SCI Class III)** in ducted or single pass configuration solely operates in a negative pressure, with its on-board fan providing -37 Pa (min) to -125 Pa (max) in the process chamber.

It provides an ISO Class 5 unidirectional total exhaust airflow, ensuring the sterility of the work zone during the whole manufacturing process. It is also equipped with double exhaust HEPA filters via Bag-In, Bag-Out (BIBO) system to prevent untoward exposure during filter change procedures.

Total Exhaust

- Ambient air is pulled through the inlet pre-filter and main filter via the main fans at the top of the isolator. This creates positive pressure on the plenum which provides the downflow of air.
 - The pre-filter extends the life of the filters by trapping larger particulates that can easily clog the main filters.
- This downflow supply then provides an ISO Class 5 environment and unidirectional airflow inside the isolator; thus, protecting the materials inside the main chamber and pass-through.
- Air from the work zone and pass-through is then quickly purged by the fans to keep the area clean. The purge is completely exhausted through HEPA filters as well; ensuring that only clean air is exhausted back to the environment.



Guide to Isolator Class III Models

SCI-2G8-N3SL-III-EG

Isolator Unit	Model	No. of gloves - Nominal Width		Electrical Requirements		
Streamline® Compounding Isolator	SCI	2G	5 ft (1.6m)	8	220-240 V AC, 50/60Hz, 1Ø	N3
		3G	6 ft (1.95m)	9	110-120 V AC, 50/60Hz, 1Ø	

Upon ordering, input material of construction at the end of the model code: SCI-2G_-N3SL-III-SS or -EG


•• SS: Full stainless steel exterior

•• EG: Electrogalvanized steel with ISOCIDE™ coating



Add-Ons and Accessories


- Manual Glove Leak Tester
 - With Optional Cleanroom Compatible Mobile Compressor
- CCTV integration
 - On right side of process chamber with acrylic viewing panel
- Back-up battery for the electromagnetic interlocks (contact Esco for more information)
- UV Lamp
- Alarm Package
- Manual Latches
- Manual Volumetric Damper
- Anti Blowback Valve
- Monitor System
 - Access to rear view monitor system
 - Beside the front panel; equipped with a keyboard and mouse arm



Adjustable foot rest



Manual Glove Leak Tester



CCTV




Audio-Visual Alarm Package for Sentinel Microprocessor Controller



Granite Slab

- SS 316 Frame
- Leveling Feet



IV bar with hooks

Code	External Construction	
Process zone: - 125 Pa (max)	EG	Electrogalvanized steel
Pass-through zone: - 75 Pa (max)	S	Stainless steel 304

Electrical Outlets and Utility Fittings

- Electrical outlet, ground fault, North America
- Electrical outlet, Euro/Worldwide

Support Stands

- Fixed height, available 720 mm (28") or 860 mm (34") - With levelling feet, or With caster wheels
- Telescoping height stand for levelling feet, nominal range 660 mm to 960 mm (26" to 37.8")
- Motorized Hydraulic Adjustable Support Stand, nominal range 685 mm to 935 mm

GENERAL SPECIFICATIONS - Streamline® Containment Isolator

Note to customer: Insert the electrical voltage number into the last model number digit _ when ordering.


Model		SCI-2G_ _	SCI-3G_ _	
Unit Nominal Size (Width)		1645 mm (5')	1950 mm (6')	
External Dimensions (W x D x H) - with 1 left pass chamber*	Exhaust Type -3 (Single Exhaust, Top BIBO)**	Without stand	1645 x 825 x 1650 mm (64.76 x 33.27 x 64.57")	1950 x 825 x 1650 (76.77 x 33.27 x 64.57")
		With SPC-A/ SPL-A (720mm, 28")	1645 x 825 x 2370 mm (64.76 x 33.27 x 92.91")	1950 x 825 x 1650 (76.77 x 33.27 x 64.57")
		With SPC-B/ SPL-B (860mm, 34")	1645 x 825 x 2510 mm (64.76 x 33.27 x 98.43")	1950 x 825 x 1650 (76.77 x 33.27 x 64.57")
		With STL (660 to 960 mm)	1645 x 825 x 2310 to 2610 mm (64.76 x 33.27 x 90.55 to 102.36")	1950 x 825 x 1650 (76.77 x 33.27 x 64.57")
		With SHM (685 to 935 mm)	1645 x 825 x 2335 to 2580 mm (64.76 x 33.27 x 91.54 to 101.18")	1950 x 825 x 1650 (76.77 x 33.27 x 64.57")
Process Chamber Internal Dimension (W x D x H)		960 x 625 x 625 mm (37.80 x 24.61 x 24.61")	1265 x 625 x 625 mm (49.80 x 24.61 x 24.61")	
Pass Chamber Internal Dimension (W x D x H)		450 x 625 x 625 mm (17.72 x 24.61 x 24.6")		
Pass Chamber Opening Dimension (W x H)	Inner door	315 x 445 mm (12.40 x 17.52")		
	Outer door	355 x 445 mm (13.98 x 17.52")		
Pass Chamber and Process Chamber Door Material		Polycarbonate		
Airflow Regime		Factory Configured Single Pass		
Pressurization		Factory Configured Negative Pressure		
Glove Port Diameter		200 mm (Circular)		
Glove Port Quantity		2	3	
Chamber Environment		ISO Class 5 for all chambers (Grade A)		
Process Chamber Downflow Velocity		0.4 +/- 20% m/s (1.31 fps)		
Pre-filter		G4, panel, polyester fiber media		
Downflow and Exhaust Filter Type		HEPA (H14) Filter with Integral Metal Guards and Filter Frame Gaskets; Fully Compliant With EN 1822 (H14) and IEST-SPCC001.3 Requirements		
Filter Efficiency		>99.995% for particle 0.1-0.3 microns (MPPS, as per EN1822)		
Lighting Level		>650 Lux		
Sound Level		≤ 67 dBA		
Isolator Construction	Inner door	1.2 mm (0.05") 18 gauge electro-galvanized steel with white oven-baked epoxy-polyester antimicrobial powder-coated finish		
	Outer door	1.5 mm (0.06") 16 gauge stainless steel, type 316L, with 4B finish		
Electrical	220-240V, AC, 50 Hz, 1Ø	SCI-2G8-_-_-_-	SCI-3G8-_-_-_-	
	Cabinet Full Load Amps (FLA)	10 A	11 A	
	Optional Outlets FLA	5 A	5 A	
	Cabinet Nominal Power	238 W, 1.5 A	333 W, 2.3 A	
	Cabinet BTU	812 BTU/hr	1136 BTU/hr	
	110-120V, AC, 50 Hz, 1Ø	SCI-2G9-_-_-_-	SCI-3G9-_-_-_-	
	Cabinet Full Load Amps (FLA)	Contact Esco for more details		
	Optional Outlets FLA			
	Cabinet Nominal Power			
	Cabinet BTU			

Electrical	Carbon Filter	Contact EscO for more details	
	CCTV Provision	5180345	
	Drain	Contact EscO for more details	
	Electrical Outlet	Contact EscO for more details	
	Alarm package	5170227	
	Pre-filter, G4	5090114	
	Glove Leak Tester - Circular	With client-supplied compressed air: 5180311 With Mobile Compressor: 5180312	
	IV Bar with S hooks	5170930	5170931
	UV Lamp	5170251	5170255
	Rear View Screen Adaptation	5180033	
	Multiple-piece Trays	Contact EscO for more details	
	Anti-blow Back Valve (ABBV)	EG-Steel: 5170352 Stainless Steel: 5170354	
	Additional Manual Latches	5180038	
	Top Exhaust Collar	EG-Steel: 5171251 Stainless Steel: 5171253	
	Side Exhaust Collar	EG-Steel: 5171252 Stainless Steel: 5171254	
Automated Pressure Hold Test	With client-supplied compressed air: 5180031 With Mobile Compressor: 5180032		
Shipping Weight	500 kg (1102.31 lbs)	700 kg (1543.68 lbs)	
Shipping Dimensions, Maximum (W x D x H)	1720 x 900 x 2250 mm (67.72 x 35.43 x 88.58")	2100 x 1150 x 2250 mm (82.68 x 45.28 x 88.58")	


- Note:
- * No different of height for the unit with and without sharps bin disposal below the workzone
 - * To add ABBV, please add +420mm for the overall height
 - * To add Top Exhaust collar with/without Exhaust Carbon Filter, please add +205mm for the overall height
 - * To add Side Exhaust collar with/without Exhaust Carbon Filter, please add +165mm for the overall height
 - ** To comply with biosafety standards, NSF 49, BS EN 12469, YY0569 Chinese standards, or other local standards, the unit must be linked to external blower or building exhaust to meet each standard's negative pressure requirement

Engineering Drawing




SCI-2G8-N3SL-III-SS




SECTION C-C




22



1. Esco Sentinel™ Microprocessor Control System with Alarm
2. Circular Glove Ports ID200mm
3. Process Chamber Polycarbonate Door
4. Support Stand SPC-5A0-S-G2
5. Exhaust Collar (Side)
6. Pass Chamber Polycarbonate Outer Door
7. Inner Door Foot Switch
8. 2nd Exhaust HEPA H14 Filter, Bag-In Bag-Out (BIBO)
9. Process Chamber Supply Fan Process Chamber
10. Supply HEPA H14 Filter
11. IV Bar (Provision Only)
12. UV Tube (Optional)
13. Pass Chamber Polycarbonate Inner Door
14. 1st Process Chamber Exhaust HEPA H14 Filter
15. LED Light
16. Exhaust Fan
17. Pass Chamber Supply Fan
18. Pass Chamber Supply HEPA H14 Filter
19. Electrical Outlet (Provision Only)
20. Pass Chamber Sliding Tray
21. 1st Pass Chamber Exhaust HEPA H14 Filter
22. G4-Air Inlet Pre-Filter






SECTION B-B




SECTION A-A

Engineering Drawing

SCI-3G8-N3SL-III-EG



SECTION A-A



SECTION B-B

1. Esco Sentinel™ Microprocessor Control System with Alarm
2. Circular Glove Ports 200X200mm
3. Main Chamber Polycarbonate Door
4. Support Stand SPC-6A0-S-SS G2
5. Exhaust Collar (Top of Unit)
6. Pass Chamber Polycarbonate Outer Door
7. Inner Door Foot Switch
8. 2nd Exhaust HEPA H14 Filter, Bag-In Bag-Out (BIBO)
9. Main Chamber Supply Fan
10. Main Chamber Supply HEPA H14 Filter
11. IV Bar (Provision Only)
12. UV Tube (Optional)
13. Pass Chamber Polycarbonate Inner Door
14. Main Chamber 1st Exhaust HEPA H14 Filter
15. Exhaust Fan
16. Pass Chamber Supply Fan
17. Pass Chamber Supply HEPA H14 Filter
18. Electrical Outlet (Provision Only)
19. Pass Chamber Sliding Tray
20. Pass Chamber 1st Exhaust HEPA H14 Filter
21. LED Light
22. G4-Air Inlet Pre-Filter

Safe Glove Change Procedure: Replacing Disposable Gloves

Safe change design system allows glove change at the middle of a process or when the equipment is in operation.



1. Pull the Glove/Sleeve outside the isolator.



2. Fold the fingers of the glove inside the cuff ring.



3. Remove the outer ring.



4. Carefully roll the gloves from the middle groove to the outer groove.



5. Take the new glove and ensure the thumb is at the top. Stretch the ring of the new glove over the port and over the old glove onto the middle groove.



6. Install the ring up to the middle groove.



7. Carefully loosen the old glove from the outer groove.



8. Put the glove/sleeve inside the isolator.



9. Working with one hand in the adjacent glove, carefully pull the old glove.



10. The procedure is now complete.

Safe Sleeve Change Procedure: Replacing the Sleeves



1. Remove the screws that secure the glove port cover



2. Remove the outer glove port cover



3. Remove the "O" ring



4. Carefully roll the ring of the sleeves/gloves from the inner groove to the outer groove of the port



5. Ensure that the old sleeves/gloves is inside the isolator



6. Take the new sleeves and ensure the thumb is at the top and stretch the "O" ring of the new sleeves over the port and over the old sleeves into the inner groove



7. Replace the "O" ring into the outer groove of the glove port



8. Working with one hand in the adjacent sleeves, carefully work from the outer ring and into the isolator. The old sleeves needs to be remove while under the new sleeves




9. Return the glove port outer cover.



10. Secure the port cover with the screws. The procedure is now complete

ESCO LIFESCIENCES GROUP NETWORK
42 Locations in 21 Countries All Over the World



- Global Offices
- Distributors
- Factories
- R&D Centers
- Regional Distribution Centers



- Air Shower
- Aseptic Containment Isolator (ACTI)
- Ceiling Laminar Airflow Units
- Cleanroom Transfer Hatch
- Containment Barrier Isolator (CBI)
- Downflow Booth (DFB)
- Dynamic Floor Laminar Hatch
- Dynamic Pass Box
- Evidence Drying Cabinet
- Garment Storage Cabinet
- General Processing Platform Isolator (GPPI)
- Laminar Flow Horizontal Trolley
- Laminar Flow Straddle Units, Single and Double
- Laminar Flow Vertical Trolley
- Pass Box
- Soft Wall Cleanroom
- Sputum Booth
- Ventilated Balance Enclosure (VBE)
- Weighing and Dispensing Containment Isolator (WDCI)

Since 1978, Esco has emerged as a leader in the development of controlled environment, laboratory and pharmaceutical equipment solutions. Products sold in more than 100 countries include biological safety cabinets, fume hoods, ductless fume hoods, laminar flow clean benches, animal containment workstations, cytotoxic cabinets, hospital pharmacy isolators, and PCR cabinets and instrumentation. With the most extensive product line in the industry, Esco has passed more tests, in more languages, for more certifications, throughout more countries than any biosafety cabinet manufacturer in the world. Esco remains dedicated to delivering innovative solutions for the clinical, life science, research and industrial laboratory community.



Esco Healthcare
 19 Changi South Street 1,
 Singapore 486779
 Tel: +65 65420833
 Email: mail@vaccixcell.com

Esco Technologies, Inc.
 2512 Metropolitan Drive, Suite 120 B
 Feasterville- Trevose, PA 19053-6738
 Tel: +1 215 322 2155
 Email: eti.pharma@escolifesciences.com

Esco GB Ltd
 Unit 2 R-evolution @ Gateway 36, Kestrel
 Way, Barnsley, S70 5SZ
 Tel: +44 (0) 1226 360 799
 Email: egb.info@escolifesciences.co

Esco Lifesciences Offices: Bangladesh | China | Denmark | Germany | Hong Kong | Indonesia | Italy | Lithuania | Malaysia | Myanmar | Philippines | Russia | Singapore | South Africa | South Korea | Taiwan | Thailand | UAE | UK | USA | Vietnam

